GMCraft 60-Minute Product Data Sheet

Manufacturer: GMC Roofing & Building Paper Products, INC. 6400 Zerker Road, Shafter, CA 93263 Contact: (661) 399 4324 Website: www.gmcpaper.com

Packaging:

- 144 Rolls Per Pallet
- 26 Pallets Per Truckload

Product Description: GMCraft 60 is an asphalt-saturated type "D" building paper, designed as a robust water-resistive barrier suitable for stucco and other exterior wall claddings. It meets and exceeds multiple building code requirements, providing excellent protection against moisture and condensation.

Key Benefits and Features:

- **Versatility:** Available in single and double-ply formats for additional strength.
- **Strong Protection:** Prevents internal damage due to moisture, suitable for stucco and exterior cladding.
- **Complies with Building Codes:** Meets or exceeds IBC and IRC standards from 2006-2021.

Technical Specifications:

- **Water Vapor Transmission:** 30 perms (ASTM E-96-00)
- **Water Resistance:** Exceeds 120 minutes (ASTM D-779)
- **Tensile Strength:** MD 60 lb-f/in, CD 44 lb-f/in (ASTM D-828)

GMCraft 10-Minute Product Data Sheet

Manufacturer: GMC Roofing & Building Paper Products, INC. 6400 Zerker Road, Shafter, CA 93263 Contact: (661) 399 4324 Website: www.gmcpaper.com

Packaging:

- 144 Rolls Per Pallet
- 28 Pallets Per Truckload

Product Description: GMCraft 10 is an asphalt-saturated type "D" building paper, offering a reliable and cost-effective water-resistive barrier solution. It meets all building codes and is designed to prohibit water or moisture intrusion behind stucco and other exterior wall claddings.

Key Benefits and Features:

- **Code Compliance:** Adheres to IBC and IRC standards from 2006-2021
- **Moisture Protection:** Prevents water penetration and protects structural integrity.
- **Versatility:** Available in single and double-ply formats for additional strength.
- **Flexible Application:** Available in various lengths

Technical Specifications:

- **Water Vapor Transmission:** 38 perms (ASTM E-96-00)
- **Water Resistance:** Exceeds 20 minutes (ASTM D-779)
- **Tensile Strength:** MD 45 lb-f/in, CD 21 lb-f/in (ASTM D-828)

GMCraft 30-Minute Product Data Sheet

Manufacturer: GMC Roofing & Building Paper Products, INC. 6400 Zerker Road, Shafter, CA 93263 Contact: (661) 399 4324 Website: www.gmcpaper.com

Packaging:

- 144 Rolls Per Pallet
- 28 Pallets Per Truckload

Product Description: GMCraft 30 is an asphalt-saturated type "D" building paper, engineered as a reliable and efficient water-resistive barrier. It is designed to prevent water or moisture intrusion behind stucco and other exterior wall claddings, ensuring structural integrity.

Key Benefits and Features:

- **Certified Performance:** Complies with IBC and IRC codes from 2006-2021.
- **Enhanced Moisture Control:** Provides superior defense against moisture intrusions.

- **Versatility:** Available in single and double-ply formats for additional strength.
- **Flexible Application:** Available in various lengths

Technical Specifications:

- **Water Vapor Transmission:** 35 perms (ASTM E-96-00)
- **Water Resistance:** Exceeds 30 minutes (ASTM D-779)
- **Tensile Strength:** MD 40+ lb-f/in, CD 20+ lb-f/in (ASTM D-828)

GMCraft 60/30-Minute Product Data Sheet

Manufacturer: GMC Roofing & Building Paper Products, INC. 6400 Zerker Road, Shafter, CA 93263 Contact: (661) 399 4324 Website: www.gmcpaper.com

Packaging:

- 144 Rolls Per Pallet
- 28 Pallets Per Truckload

Product Description: GMCraft 60/30 is a high-performance water-resistive barrier designed to exceed industry standards. As an asphalt-saturated type "D" building paper, it provides superior protection against moisture intrusion behind stucco and other exterior wall claddings. It complies with multiple IBC and IRC from 2006-2021.

Key Benefits and Features:

- **Weather Resistance:** Exceeds Federal Specification UU-B-790a for weather-resistive sheathing paper.
- **Durability:** Maintains ICC Evaluation Reports and meets ASTM standards for strength and moisture resistance.
- **Double-Ply Option:** Enhances wall assembly performance with two layers of Grade "D" paper.

Technical Specifications:

- **Water Vapor Transmission:** 30 perms (ASTM E-96-00)
- **Water Resistance:** Exceeds 120 minutes (ASTM D-779)
- **Tensile Strength:** MD 90+ lb-f/in, CD 64+ lb-f/in (ASTM D-828)