GMC 30 ASTM D 226 Type II

Manufacturer: GMC Roofing & Building Paper Products, INC. 6400 Zerker Road, Shafter, CA 93263 Contact: (661) 399 4324 Website: www.gmcpaper.com

Packaging:

- 25 Rolls Per Pallet
- 34 Pallets Per Truckload

Product Description: The GMC 30 ASTM D 226 TYPE II is a superior quality asphalt-saturated organic felt underlayment, recognized for its reliability and eco-friendly manufacturing. It provides a robust secondary weather-resistant barrier for all roofing applications.

Key Benefits and Features:

- **Enduring Reliability:** Trusted by architects and building code officials.
- **Ease of Use:** Simple installation without the need for special fasteners.
- **Environmental Responsibility:** Made from recycled materials, supporting green building initiatives.

Uses:

- Acts as a breathable barrier over roof decks prior to primary roofing installation.
- Recommended for Metal and Tile Roofing (Concrete and Clay) with 60 days exposure time

Certifications:

- ASTM D 226 Type II, ASTM D 4869 Type IV

Technical Specifications:

- **Width:** 39 3/8 Inches
- **Coverage:** 216 Sq. Ft

GMC 15 ASTM D 226 Type I

Manufacturer: GMC Roofing & Building Paper Products, INC. 6400 Zerker Road, Shafter, CA 93263 Contact: (661) 399 4324 Website: www.gmcpaper.com

Packaging:

- 25 Rolls per Pallet

- 34 Pallets per Truckload

Product Description: GMC 15 ASTM D 226 TYPE I is an industry-leading authentic asphalt-saturated organic felt underlayment, renowned for its superior performance and eco-friendly construction.

Key Benefits and Features:

- **Proven Success:** Endorsed by roofing professionals and trade organizations.
- **Adaptable Performance:** Suitable for all climate conditions and structure types.
- **Sustainable Manufacturing:** Made with 100% post-consumer recycled materials.

Uses:

- Serves as a breathable secondary barrier over decks before installing asphalt shingles.

Certifications:

- ASTM D 226, Type I

Technical Specifications:

- **Width:** 39 3/8 Inches
- **Coverage:** 432 Sq. Ft

GMC #40 OBS ASTM D2626

Manufacturer: GMC Roofing & Building Paper Products, INC. 6400 Zerker Road, Shafter, CA 93263 Contact: (661) 399 4324 Website: www.gmcpaper.com

Packaging:

- 25 Rolls Per Pallet
- 25 Pallets Per Truckload

Product Description: GMC #40 OBS is a premium-grade organic felt base sheet, expertly crafted with asphalt saturation and weathering-grade asphalt coating. Topped with mineral surface fines to prevent rolls from sticking.

Key Benefits and Features:

- **Long-Lasting Durability:** Coated with weathering-grade asphalt for extended life.
- **Versatile Application:** Suitable for clay or concrete tile underlayment.
- **Certified Excellence:** Complies with ASTM D 2626, guaranteeing top-tier quality.

Uses:

- Ideal for residential roofing tile systems.
- Applied over flat roofing decks or insulation before Built-Up Roofing systems.

Certifications:

- ASTM D2626

Technical Specifications:

- **Width:** 39 3/8 Inches
- **Length:** 65 feet 10 Inches
- **Coverage:** 216 Sq. Ft
- **Average Weight of Roll:** 78.0 lbs
- **Breaking Strength:** MD 35 lbf/in, CD 20 lbf/in
- **Exposure:** Can be left exposed for 180 days.

GMC 30 ASTM 4869 Type II

Manufacturer: GMC Roofing & Building Paper Products, INC. 6400 Zerker Road, Shafter, CA 93263 Contact: (661) 399 4324 Website: www.gmcpaper.com

Packaging:

- 36 Rolls per Pallet
- 36 Pallets per Truckload

Product Description: GMC 30 ASTM 4869 Type II offers unmatched quality as an authentic asphalt-saturated organic felt underlayment. This green roofing product is manufactured with recycled paper, providing a sustainable yet powerful secondary weather-resistant barrier.

Key Benefits and Features:

- **Green Innovation:** Utilizes 100% recycled materials while enhancing performance.
- **Effortless Application:** No special fasteners needed, reducing installation time.
- **Comprehensive Protection:** Breathable membrane helps prevent structural damage.

Uses:

- Acts as a breathable barrier over roof decks before primary roofing installation.
- Recommended for asphalt shingles

Certifications:

- ASTM D 4869, Type II

Technical Specifications:

- **Width:** 39 3/8 Inches
- **Coverage:** 216 Sq. Ft

GMC 15 ASTM 4869 Type I

Manufacturer: GMC Roofing & Building Paper Products, INC. 6400 Zerker Road, Shafter, CA 93263 Contact: (661) 399 4324 Website: www.gmcpaper.com

Packaging:

- 36 Rolls per Pallet
- 36 Pallets per Truckload

Product Description: GMC 15 ASTM 4869 Type I is a leading-edge green roofing product, made from recycled paper and authentic asphalt-saturated organic felt. It's engineered to offer superior performance as a breathable secondary weather-resistant barrier.

Key Benefits and Features:

- **Eco-Friendly Design:** Crafted from 100% post-consumer recycled materials.
- **Maximum Durability:** Engineered for peak performance in all conditions.
- **Cost-Effective Efficiency:** Economical and covers 4 squares of roof area

Uses:

- Serves as a breathable secondary barrier over the roof deck before primary roofing installation.

Certifications:

- ASTM D 4869 Type I

Technical Specifications:

- **Width:** 39 3/8 Inches
- **Coverage:** 432 Sq. Ft

GMC 18” 30 ASTM D 226 Type II

Manufacturer: GMC Roofing & Building Paper Products, INC. 6400 Zerker Road, Shafter, CA 93263 Contact: (661) 399 4324 Website: www.gmcpaper.com

Packaging:

- 32 Rolls per Pallet

Product Description: GMC 18" 30 ASTM D 226 is a superior quality asphalt-saturated organic felt underlayment, designed to offer reliable secondary weather resistance in conjunction with primary shake or shingle roofing starter.

Key Benefits and Features:

- **Proven Reliability:** Trusted by professionals for over a century.
- **Versatile Performance:** Suitable for various climate conditions and structure types.
- **Eco-Conscious Manufacturing:** Made from recycled materials for sustainable building.

Uses:

- Used as a breathable barrier with primary shake or shingle products.

Certifications:

- ASTM D 226, Type II

Technical Specifications:

- **Width:** 18 Inches
- **Coverage:** 180 Sq. Ft

GMC 22" 30 ASTM D 226 TYPE II

Manufacturer: GMC Roofing & Building Paper Products, INC. 6400 Zerker Road, Shafter, CA 93263 Contact: (661) 399 4324 Website: www.gmcpaper.com

Packaging:

- 32 Rolls per Pallet

Product Description: The GMC 22" 30 ASTM D 226 TYPE II Premium Shake Felt offers an innovative solution for roofing applications, providing two-layer coverage in a single application. Ideal for both natural and artificial shake roofing systems.

Key Benefits and Features:

- **Cost-Effective:** Saves labor with efficient installation.
- **Eco-Friendly:** Crafted from recycled materials, supporting sustainable building practices.

Uses:

- Designed for use with natural and artificial shake roofing systems.

Certifications:

- ASTM D 226 Type II

Technical Specifications:

- **Width:** 22 Inches
- **Coverage:** 220 Sq. Ft

GMC 18” 15 ASTM D 4869 Type I

Manufacturer: GMC Roofing & Building Paper Products, INC. 6400 Zerker Road, Shafter, CA 93263 Contact: (661) 399 4324 Website: www.gmcpaper.com

Packaging:

- Packaging details would be specified based on product options.
- Normally 40 Rolls/pallet

Product Description: GMC 18” 15 ASTM D 4869 Type I is a high-quality asphalt-saturated organic felt underlayment, providing effective secondary weather resistance for roofing applications.

Key Benefits and Features:

- **Reliable Performance:** Trusted by numerous installations for consistent reliability.
- **Eco-Conscious:** Made from recycled materials, supporting sustainable construction.
- **Flexible Use:** Compatible with a variety of roofing systems.

Uses:

- Provides a breathable secondary barrier for roof decks before primary roofing installation.

Certifications:

- ASTM D 4869 Type I

Technical Specifications:

- **Width:** 18 Inches
- **Coverage:** 4 Squares

Premium MSR Mineral Surfaced Roll Roofing

Manufacturer: GMC Roofing & Building Paper Products, INC. 6400 Zerker Road, Shafter, CA 93263 Contact: (661) 399 4324 Website: www.gmcpaper.com

Packaging:

 20 rolls/pallet

30 Pallets/ Truck

Product Description: Premium MSR Mineral Surfaced Roll Roofing is a high-quality asphalt roll roofing product. This product is manufactured with fiberglass mat, coated with premium quality coating asphalt and covered with 3M granules for the highest degree of ultra violet protection.

Key Benefits and Features:

General purpose economical choice roll roofing product that can be used with cold adhesive or hot mopping application for low-slope roofs.

Used for residential low slope roofing applications such as porches, carports or as a flashing material.

Used as a cap sheet in the construction of build-up roofs as well as superior performance tile underlayment.

 Enhanced Weather Resistance: Mineral surface provides superior protection against the elements.

 Easy Installation: Designed for simple and efficient application, saving time and labor.

 Aesthetic Appeal: Available in various colors to match different architectural styles.

 Durable Construction: Manufactured to withstand harsh weather conditions, ensuring long-lasting performance**.**

Uses:

 Ideal for residential and commercial roofing projects, particularly where budget-friendly**,** durable solutions are required**.**

 Suitable for low-slope roofing applications**.**

Certifications:

ASTM D 3909

Technical Specifications:

 Width: 39.375

 Coverage: 108 Sq ft covers 100 square feet of roof

 Weight: 78 lb

GBS 40 Premium All Weather Base

Manufacturer: GMC Roofing & Building Paper Products, INC. 6400 Zerker Road, Shafter, CA 93263 Contact: (661) 399 4324 Website: www.gmcpaper.com

Packaging:

- 30 Rolls Per Pallet
- 20 Pallets Per Truckload

Product Description: GBS 40 Premium All Weather Base is designed for maximum protection under clay, concrete tile, and metal roofing systems. Manufactured with a fiberglass sheet and

specially formulated SBS Modified asphalt, it provides superior durability in both cold and warm weather conditions.

Key Benefits and Features:

- **Weather-Resistant:** Engineered to withstand extreme temperatures.
- **High-Quality Construction:** Meets ASTM D226, ASTM D4601, and ASTM D6757 Type II standards.
- **Versatile Usage:** Provides protection for various roofing materials, including concrete and clay tiles.

Uses:

- Serves as an underlayment for concrete tile, clay tile, and metal roofing systems.

Certifications:

- ASTM D226, ASTM D4601, ASTM D6757 Type II, ICC Approval - ESR 1561

Technical Specifications:

- **Width:** 39 3/8 Inches
- **Coverage:** 216 Sq. Ft
- **Weight / Roll:** 80.0 lbs (36.3 kg)
- **Perm Rating:** Zero