
Roofing & Building Paper Products, INC

GMC

ROOFING AND BUILDING PRODUCTS CATALOG



2024

WHO WE ARE & WHAT WE DO BEST


GMC Roofing and Building Paper Products is a leading manufacturer of quality asphalt saturated roll roofing products, modified bitumen membranes and building paper products. GMC was established in 2002 by Glen Passmore and Mathew Chakola who brought decades of experience in manufacturing roofing and organic felt to the company. Their goal was, and still remains, to provide premium roofing and building materials to professional installers serving the housing market in the United States.

GMC produces its materials in three facilities located in California, Florida and Oklahoma. To maintain consistent quality products, GMC is vertically integrated by manufacturing its own organic dry felt using post-industrial recycled material. GMC is committed to its recycling efforts and the important role it plays in its manufacturing process. This manufacturing strategy allows GMC to provide consistency in product performance and pricing to its customers.

The foundation of GMC's success is based on building strong relationship with its customers, suppliers and employees. GMC is committed to creating immediate and lasting relationships with its customers and developing additional products to serve their needs.



roll roofing, modified bitumen, building paper



3 USA manufacturing locations



customer-focused company



vertically integrated manufacturing



post-industrial recycled content



financially strong

OUR ROOFING PRODUCTS

30 ASTM D 226 TYPE II

Asphalt Saturated Organic Felt Underlayment

Used as a breathable secondary weather resistant barrier when applied over the roof deck prior to the installation of the primary roofing product.

2 square roll



- Reliable and proven technology.
- Approved and recommended for use in most roofing applications.
- Versatile and performs in all climate conditions.
- Easy to apply, no special fasteners required.
- Permeable, breathable membrane to help prevent dry rot, mold and other structural damages.
- Natural non-skid surface ideal for steep slope roofing.
- Durable after prolonged exposure - 60 days in single ply and 6 months in two-ply applications.
- Organic dry felt is made from 100% post-consumer recycle material and domestic asphalt from a local source.

Width:	39 3/8 "
Coverage:	216 Sq. Ft.
Packaging:	25 Rolls/Pallet

15 ASTM D 226 TYPE I

Asphalt Saturated Organic Felt Underlayment

Used as a breathable secondary weather resistant barrier when applied over the deck prior to the installation of the primary roofing product. Ideal for use with asphalt shingles.

4 square roll



- Reliable and proven technology.
- Approved and recommended for use in asphalt shingle roofing applications.
- Versatile and performs in all climate conditions.
- Easy to apply, no special fasteners required.
- Breathable membrane to help prevent dry rot, mold and other structural damages.
- Natural non-skid surface ideal for steep slope roofing.
- Durable after prolonged exposure.
- Organic dry felt is made from 100% post-consumer recycle material and domestic asphalt from a local source.

Width:	39 3/8 "
Coverage:	432 Sq. Ft.
Packaging:	25 Rolls/Pallet

OUR ROOFING PRODUCTS

15 ASTM D 4869 TYPE I

Asphalt Saturated Organic Felt Underlayment

Used as a breathable secondary weather resistant barrier when applied over the deck prior to the installation of the primary roofing product. Ideal for use with asphalt shingles.

4 square roll



- Reliable, economical and proven technology.
- Approved and recommended for use in asphalt shingle roofing applications.
- Versatile and performs in all climate conditions.
- Easy to apply, no special fasteners required.
- Breathable membrane to help prevent dry rot, mold and other structural damages.
- Natural non-skid surface ideal for steep slope roofing.
- Durable after prolonged exposure.
- Organic dry felt is made from 100% post-consumer recycle material and domestic asphalt from a local source.

Width:	39 3/8 "
Coverage:	432 Sq. Ft.
Packaging:	36 Rolls/Pallet

*Also available in a 324 Sq. Ft. roll

30 ASTM D 4869 Type II

Asphalt Saturated Organic Felt Underlayment

Used as a breathable secondary weather resistant barrier when applied over the roof deck prior to the installation of the primary roofing product.

2 square roll



- Reliable and proven technology.
- Approved and recommended for use in all roofing applications.
- Versatile and performs in all climate conditions.
- Easy to apply, no special fasteners required.
- Permeable, breathable membrane to help prevent dry rot, mold and other structural damages.
- Natural non-skid surface ideal for steep slope roofing.
- Organic dry felt is made from 100% post-consumer recycle material and domestic asphalt from a local source.

Width:	39 3/8 "
Coverage:	216 Sq. Ft.
Packaging:	36 Rolls/Pallet

OUR ROOFING PRODUCTS

#40 ORGANIC
Premium Base Sheet

Used as part of a Built-Up roof system or as an underlayment in concrete and clay tile roof applications.

2 square roll



- ASTM D2626
- Superior quality organic felt saturated with asphalt and then coated on both sides with weathering grade coating asphalt with a top mineral surface.
- Reliable and proven technology.
- Approved and recommended for use under tile roof applications.
- Versatile and performs in all climate conditions.
- Easy to apply, no special fasteners required.
- Organic dry felt is made from 100% post-consumer recycle
- Up to 30 year warranty available.

Width:	39 3/8 "
Coverage:	216 Sq. Ft.
Packaging:	25 Rolls/Pallet

GBS 40
All Weather Fiberglass Base Sheet

Used as a component of an approved roof assembly.

3 square roll



- ASTM D4601
- Used as a component of an approved roof assembly.
- Versatile and performs in all climate conditions.
- Easy to apply, no special fasteners required.
- Breathable membrane to help prevent dry rot, mold and other structural damages.
- Natural non-skid surface ideal for steep slope roofing.
- Durable after prolonged exposure. Up to 90 days in single ply and 120 days in two-ply applications
- Features lay lines at 2", 4" and 18 3/4".
- Up to 30 year warranty available.

Width:	39 3/8 "
Coverage:	324 Sq. Ft.
Packaging:	25 Rolls/Pallet

OUR ROOFING PRODUCTS

MSR
Mineral Surface Roll Roofing

Used with cold adhesives or hot mopping applications for low slope roofs as cap sheet in Built-up-roof systems, or as flashing material. Also used as a superior performance tile underlayment in steep slope applications.

1 square roll



- ASTM D 3909
- Premium quality mineral surfaced roll roofing featuring a fiberglass mat and coating asphalt.
- Reliable and proven technology.
- Versatile and performs in all climate conditions.
- Easy to apply, no special fasteners required.
- Superior granule adhesion provides a non skid surface ideal for steep slope roofing.
- Can be used as a primary roofing product, as well as a premium tile underlayment.
- Available in Black, White and Cedar.

Width:	39 3/8 "
Coverage:	108 Sq. Ft.
Packaging:	30 Rolls/Pallet



30 ASTM D 226 TYPE II - 18" AND 22"
Asphalt Saturated Organic Felt Underlayment

Used as a breathable secondary weather resistant barrier when installed with the primary shake or shingle product.

18" and 22" rolls



- Reliable and proven technology.
- Approved and recommended for use in shake and asphalt shingle roofing applications.
- Versatile and performs in all climate conditions.
- Easy to apply, no special fasteners required.
- Breathable membrane to help prevent dry rot, mold and other structural damages.
- Natural non-skid surface ideal for steep slope roofing.
- Durable after prolonged exposure.
- Organic dry felt is made from 100% post-consumer recycle material and domestic asphalt from a local source.

Width:	18 "
Coverage:	180 Sq. Ft.
Packaging:	32 Rolls/Pallet

Width:	22 "
Coverage:	220 Sq. Ft.
Packaging:	32 Rolls/Pallet

ROOFING PRODUCT INFORMATION

NAME	DESCRIPTION	DIMENSIONS
30 ASTM D 226 TYPE II	Asphalt Saturated Organic Felt Underlayment	39 3/8" x 66'
15 ASTM D 226 TYPE I	Asphalt Saturated Organic Felt Underlayment	39 3/8" x 132'
15 ASTM D 4869 TYPE I	Asphalt Saturated Organic Felt Underlayment	39 3/8" x 132'
30 ASTM D 4869 TYPE II	Asphalt Saturated Organic Felt Underlayment	39 3/8" x 66'
#40 ORGANIC	Premium Asphalt Coated Base Sheet	39 3/8" x 66'
GBS 40	All Weather Asphalt Coated Fiberglass Underlayment	39 3/8" x 66'
MSR	Mineral Surface Roll Roofing	**39 3/8 ""** x 33'

BUILDING PAPER PRODUCT INFORMATION

NAME	DESCRIPTION	DIMENSIONS
GMCRAFT 10 (324)	Asphalt Saturated Building Paper	40" x 98'
GMCRAFT 10 (324 DW)	Asphalt Saturated Building Paper	40" x 49'
GMCRAFT 10 (500)	Asphalt Saturated Building Paper	40" x 150'
GMCRAFT 10 (500 DW)	Asphalt Saturated Building Paper	40" x 75'
GMCRAFT 30	Asphalt Saturated Building Paper	40" x 98'
GMCRAFT 30 (DW)	Asphalt Saturated Building Paper	40" x 49'
GMCRAFT 30 (400)	Asphalt Saturated Building Paper	40" x 120'
GMCRAFT 60	Asphalt Saturated Building Paper	40" x 72'
GMCRAFT 60 (DW)	Asphalt Saturated Building Paper	40" x 49'
GMCRAFT 60/30	Asphalt Saturated Building Paper	40" x 49'
GMC RED ROSIN	Lightweight Moisture Barrier	40" x 150'
GMC UTILITY PAPER	Lightweight Moisture Barrier	40" x 150'

OUR BUILDING PAPER PRODUCTS

GMC CRAFT 10 – 324
Asphalt Saturated Building Paper

Used as a scondary weather resistant barrier when installed behind stucco and other exterior wall cladding.



- Weather-restrictive barrier
- Complies with 2018 IBC (International Building Code) and 2018 IRC (International Residential Code)
- Exceeds the standards set in Federal Specification UU-B-790a, Type 1, Grade "D", Style 2, in accordance with Section 1402.1 of the Uniform Building Code
- ESR-2376

Single - 98 lineal feet
Double - 49 lineal feet

Dimensions:	**Single 40" x 98' Double 40" x 49'**
Single Coverage: Double Coverage:	**324 Sq. Ft. 162 Sq. Ft.**
Packaging:	**144 Rolls/Pallet**

TEST METHOD	DESCRIPTION	TEST RESULTS	STANDARD
ASTM E-96-00	Water Vapor Transmission	**38 Perms**	35 Perms
ASTM D-779	Water Resistance	**Exceeds 20 minutes**	10 minutes
ASTM D-828	Tensile Strength	**MD 45 lb-f/in CD 21 lb-f/in**	MD 20 lb.-f/in CD 20 lb.-f/in

GMC CRAFT 10 – 500
Asphalt Saturated Building Paper

Used as a scondary weather resistant barrier when installed behind stucco and other exterior wall cladding.



- Weather-restrictive barrier
- Complies with 2018 IBC (International Building Code) and 2018 IRC (International Residential Code)
- Exceeds the standards set in Federal Specification UU-B-790a, Type 1, Grade "D", Style 2, in accordance with Section 1402.1 of the Uniform Building Code
- ESR-2376

Single - 150 lineal feet
Double - 75 lineal feet

Dimensions:	**Single 40" x 150' Double 40" x 75'**
Single Coverage: Double Coverage:	**500 Sq. Ft. 250 Sq. Ft.**
Packaging:	**100 Rolls/Pallet**

TEST METHOD	DESCRIPTION	TEST RESULTS	STANDARD
ASTM E-96-00	Water Vapor Transmission	**38 Perms**	35 Perms
ASTM D-779	Water Resistance	**Exceeds 30 minutes**	10 minutes
ASTM D-828	Tensile Strength	**MD 45 lb-f/in CD 21 lb-f/in**	MD 20 lb.-f/in CD 20 lb.-f/in

OUR BUILDING PAPER PRODUCTS

GMC CRAFT 30
Asphalt Saturated Building Paper

Used as a scondary weather resistant barrier when installed behind stucco and other exterior wall cladding.



- Weather-restrictive barrier
- Complies with 2018 IBC (International Building Code) and 2018 IRC (International Residential Code)
- Exceeds the standards set in Federal Specification UU-B-790a, Type 1, Grade "D", Style 2, in accordance with Section 1402.1 of the Uniform Building Code
- ESR-2376

Single - 98 lineal feet
Double - 49 lineal feet

Dimensions:	**Single 40" x 98' Double 40" x 49'**
Single Coverage: Double Coverage:	**324 Sq. Ft. 162 Sq. Ft.**
Packaging:	**144 Rolls/Pallet**

TEST METHOD	DESCRIPTION	TEST RESULTS	STANDARD
ASTM E-96-00	Water Vapor Transmission	**35 Perms**	35 Perms
ASTM D-779	Water Resistance	**Exceeds 30 minutes**	30 minutes
ASTM D-828	Tensile Strength	**MD 40 lb-f/in CD 20 lb-f/in**	MD 20 lb.-f/in CD 20 lb.-f/in

GMC CRAFT 30 - 400
Asphalt Saturated Building Paper

Used as a scondary weather resistant barrier when installed behind stucco and other exterior wall cladding.



- Weather-restrictive barrier
- Complies with 2018 IBC (International Building Code) and 2018 IRC (International Residential Code
- Exceeds the standards set in Federal Specification UU-B-790a, Type 1, Grade "D", Style 2, in accordance with Section 1402.1 of the Uniform Building Code
- ESR-2376

Single - 120 lineal feet

Dimensions:	**Single 40" x 120'**
Single Coverage:	**400 Sq. Ft.**
Packaging:	**144 Rolls/Pallet**

TEST METHOD	DESCRIPTION	TEST RESULTS	STANDARD
ASTM E-96-00	Water Vapor Transmission	**35 Perms**	35 Perms
ASTM D-779	Water Resistance	**Exceeds 30 minutes**	30 minutes
ASTM D-828	Tensile Strength	**MD 40 lb-f/in CD 20 lb-f/in**	MD 20 lb.-f/in CD 20 lb.-f/in

OUR BUILDING PAPER PRODUCTS

GMC CRAFT 60
Asphalt Saturated Building Paper

Used as a scondary weather resistant barrier when installed behind stucco and other exterior wall cladding.



- Weather-restrictive barrier
- Complies with 2018 IBC (International Building Code) and 2018 IRC (International Residential Code)
- Exceeds the standards set in Federal Specification UU-B-790a, Type 1, Grade "D", Style 2, in accordance with Section 1402.1 of the Uniform Building Code
- ESR-2376

Single - 72 lineal feet
Double - 49 lineal feet

Dimensions:	**Single 40" x 72' Double 40" x 49'**
Single Coverage: Double Coverage:	**240 Sq. Ft. 162 Sq. Ft.**
Packaging:	**144 Rolls/Pallet**

TEST METHOD	DESCRIPTION	TEST RESULTS	STANDARD
ASTM E-96-00	Water Vapor Transmission	**38 Perms**	35 Perms
ASTM D-779	Water Resistance	**Exceeds 60 minutes**	60 minutes
ASTM D-828	Tensile Strength	**MD 60 lb-f/in CD 44 lb-f/in**	MD 20 lb.-f/in CD 20 lb.-f/in

GMC CRAFT 60/30
Asphalt Saturated Building Paper

One layer of each, not glued. Used as a scondary weather resistant barrier when installed behind stucco and other exterior wall cladding.



- Weather-restrictive barrier
- Complies with 2018 IBC (International Building Code) and 2018 IRC (International Residential Code)
- Exceeds the standards set in Federal Specification UU-B-790a, Type 1, Grade "D", Style 2, in accordance with Section 1402.1 of the Uniform Building Code
- ESR-2376

Double - 49 lineal feet

Dimensions:	**Double 40" x 49'**
Double Coverage:	**162 Sq. Ft.**
Packaging:	**144 Rolls/Pallet**

TEST METHOD	DESCRIPTION	TEST RESULTS	STANDARD
ASTM E-96-00	Water Vapor Transmission	**45 Perms**	35 Perms
ASTM D-779	Water Resistance	**> 1.5 hours**	90 minutes
ASTM D-828	Tensile Strength	**MD 90+ lb-f/in CD 64+ lb-f/in**	MD 20 lb.-f/in CD 20 lb.-f/in

OUR BUILDING PAPER PRODUCTS

GMC RED ROSIN
Lightweight Moisture Paper

Lightweight single ply kraft paper soaked in red organic dye. Used to protect surfaces from general construction.



- Serves as a separation barrier, protecting against wind and dust intrusion while reducing squeaking
- Environmentally safe and made from 100% recyclable fibers
- Easy to install and remove

Dimensions:	Single 40“ x 150’
Single Coverage:	500 Sq. Ft.
Packaging:	72 Rolls/Pallet

Single - 150 lineal feet

GMC UTILITY PAPER
Lightweight Moisture Barrier

Lightweight single ply kraft paper. Used to protect surfaces from general construction.



- Serves as a separation barrier, protecting against wind and dust intrusion while reducing squeaking
- Environmentally safe and made from 100% recyclable fibers
- Easy to install and remove

Dimensions:	Single 40“ x 150’
Single Coverage:	500 Sq. Ft.
Packaging:	Rolls/Pallet

Single - 150 lineal feet



GMC ROOFING & BUILDING PAPER PRODUCTS, INC.

6400 Zerker Road
Shafter, CA 93263
(661) 399-4324
www.gmcpaper.com

MADE IN USA

08/2022