GBS 40 PREMIUM ALL WEATHER BASE

Fiberglass Underlayment

Product Data

GBS 40 (G2) PREMIUM All Weather Base is manufactured to the highest quality standards. GBS 40 G2 is manufactured from a fiberglass mat then coated on both sides with a Specially Formulated weathering grade asphalt, to prevent cracking in cold weather and stay durable in warm weather, then covered on top with sand fines to prevent sticking. Maximum protection underlayment for most roofing systems.

Certifications

Manufactured to comply with:
ASTM D4601
FBC Approved Product



Manufactured in the USA
Producing American Jobs!

Installation

Follow building code and local amendments when installing **GMC GBS 40 *all weather base.*** Refer to the Tile Roofing Institute (TRI) manual when used as a clay or concrete tile underlayment.. Can be exposed for up to 90 days single ply and 120 days for double ply.
NO Special fasteners required

Technical Data

Typical Properties, 3.0 square roll

Weight / Square (nominal)	25.0 lbs (11.34 kg)
Weight / Roll (nominal)	75.0 lbs (34.02 kg)
Dimensions	39 3/8" wide x 98' long (1M wide x 20.1M long)
Lay Lines	2", 4" and 18 3/4" minimum (50.8 mm, 102 mm and 476.2 mm)
Machine direction and Cross Direction	22 lbf/in
Pliability (1/2") Radius Maximum Failures	Zero

Width: 39 3/8 Inches
Coverage: 324 Sq. Ft
Packaging: 25 Rolls Per Pallet

Manufactured by
GMC Roofing & Building Paper Products, INC.
6400 Zerker Road, Shafter, CA. 93263
(661) 399 4324
www.gmcpaper.com