#40 OBS Product Data

ORGANIC BASE SHEET

#40 OBS is manufactured from superior quality organic felt that is saturated with asphalt and then coated on both sides with weathering grade asphalt and then covered on top with mineral surface fines to prevent sticking in the roll.

Certifications

Manufactured to comply with:
ASTM D2626



Manufactured in the USA
Producing American Jobs!

Installation

#40 OBS is an excellent product for use under roofing tiles. **#40 OBS** is applied over the roof deck before the application of primary roofing system. Follow building code and local amendments when installing **#40 OBS.** Refer to the Tile Roofing Institute (TRI) manual when used as a clay or concrete tile underlayment. **#40 OBS** can be used in commercial roofing systems.

Exposure

#40 OBS can be left exposed for 180 days from date of application. It is the contractors responsibility to repair any areas where damage to underlayment has occurred due to "workbench abuse" prior to application of primary roofing material.

Technical Data

Typical Properties, 2.0 square roll

- Average Weight of roll = 78.0 lbs
- Mass of Asphalt Saturant = 7.2 lbs / 100 ft sq
- Mass of desaturated felt = 5.2 lbs / 100 ft sq
- Saturation efficiency (min) by weight = 70%
- Breaking Strength at 77F (min)
- Machine direction = 35 lbf/in
- Cross Direction = 20 lbf/in
- No. of Rolls per Pallet = 25

Width: 39 3/8 Inches
Length: 65 feet 10 Inches
Coverage: 216 Sq. Ft
Packaging: 25 Rolls Per Pallet
25 Pallets Per Truckload

Warranty

GMC offers a 15 year limited material warranty on single ply and 30 year limited material warranty on double ply to approved applicators. Please contact GMC Roofing & Building Paper Products representative for full details.

GMC Roofing & Building Paper Products, INC.
6400 Zerker Road, Shafter, CA. 93263
(661) 399 4324
www.gmcpaper.com