GBS 40 PREMIUM ALL WEATHER BASE
SBS Modified Fiberglass Underlayment

Product Data

GBS 40 PREMIUM All Weather Base is manufactured to the highest quality standards. GBS 40 is manufactured from a fiberglass sheet with a Specially Formulated SBS Modified asphalt to prevent cracking in cold weather and stay durable in warm weather. Maximum protection underlayment for concrete tile, clay tile, and metal roofing systems.

Certifications

Manufactured to comply with:
ASTM D226 ASTM D4601
ASTM D6757 Type II



Manufactured in the USA
Producing American Jobs!

Installation

Follow building code and local amendments when installing **GMC GBS 40 PREMIUM all weather base.** Refer to the Tile Roofing Institute (TRI) manual when used as a clay or concrete tile underlayment. Can be exposed for up to 90 days single ply and 120 days for double ply.

Technical Data

Typical Properties, 2.0 square roll

Weight / Square (nominal)	40.0 lbs (18.1 kg)
Weight / Roll (nominal)	80.0 lbs (36.3 kg)
Dimensions	39 3/8" wide x 66' long (1M wide x 20.1M long)
Lay Lines	2", 4" and 18 3/4" minimum (50.8 mm, 102 mm and 476.2 mm)
Thickness	53 mils (nominal)
Perm Rating (ASTM E96)	Zero

As manufactured, meets the requirements of ASTM D226 and ASTM D4869 and complies with the physical requirements of ASTM D4601 Type II. ICC Approval - ESR 1561

Width: 39 3/8 Inches
Coverage: 216 Sq. Ft
Packaging: 25 Rolls Per Pallet
24 Pallets Per Truckload

Warranty

GMC offers a 15 year limited material warranty on single ply and 30 year limited material warranty on double ply to approved applicators. Please contact GMC Roofing & Building Paper Products representative for full details.

Manufactured by
GMC Roofing & Building Paper Products, INC.
6400 Zerker Road, Shafter, CA. 93263
(661) 399 4324
www.gmcpaper.com